

API Seamless Pipe / API ERW Pipe

Size			Schedule No.	Wall Thickness	Weight
Inch	Nominal	mm		mm	Kg/m
1/8	6	10.3	40(std)	1.73	0.36
			80(XS)	2.41	0.46
1/4	8	13.7	40(std)	2.24	0.63
			80(XS)	3.02	0.80
3/8	10	17.1	40(std)	2.31	0.85
			80(XS)	3.20	1.10
1/2	15	21.3	40(std)	2.77	1.27
			80(XS)	3.73	1.62
			160	4.78	1.95
3/4	20	26.7	40(std)	2.87	1.69
			80(XS)	3.91	2.2
			160	5.56	2.9
1	25	33.4	40(std)	3.38	2.5
			80(XS)	4.55	3.24
			160	6.35	4.24
1 1/4	32	42.2	40(std)	3.56	3.39
			80(XS)	4.85	4.47
			160	6.35	5.61
1 1/2	40	48.3	40(std)	3.68	4.05
			80(XS)	5.08	5.41
			160	7.14	7.25
2	50	60.3	40(std)	3.91	5.44
			80(XS)	5.54	7.48
			160	8.74	11.11
2 1/2	65	73.0	40(std)	5.16	8.63
			80(XS)	7.01	11.41
			160	9.52	14.92
3	80	88.9	40(std)	5.49	11.29
			80(XS)	7.62	15.27
			160	11.13	21.35
3 1/2	90	101.6	40(std)	5.74	13.57
			80(XS)	8.08	18.63
			160	12.2	26.52
4	100	114.3	40(std)	6.02	16.07
			80(XS)	8.56	22.32
			120	11.13	28.32
			160	13.49	33.54
5	125	141.3	40(std)	6.55	21.77
			80(XS)	9.52	30.94

	120	141.5	120	12.7	40.28
			160	15.88	49.11
6	150	168.3	40(std)	7.11	28.26
			80(XS)	10.97	42.56
			120	14.27	54.2
			160	18.26	67.56
8	200	219.1	40(std)	8.18	42.55
			80(XS)	12.7	64.64
			120	18.26	90.44
			160	23.01	111.27
10	250	273.0	40(std)	9.27	60.29
			80(XS)	15.09	95.97
			120	21.44	133
			160	28.57	172.21
12	300	323.8	40(std)	10.31	79.7
			80(XS)	17.48	132.04
			120	25.40	186.91
			160	33.32	238.68
14	350	355.6	40(std)	11.13	94.55
			80(XS)	19.05	158.1
			120	27.79	224.65
			160	35.71	281.7
16	400	406.4	40(std)	12.7	123.3
			80(XS)	21.44	203.53
			120	30.96	286.64
			160	40.49	365.35
18	450	457	40(std)	14.27	155.87
			80(XS)	23.83	254.67
			120	34.92	363.64
			160	45.24	459.59
20	500	508	40(std)	15.09	183.42
			80(XS)	26.19	311.17
			120	38.1	441.49
			160	50.01	564.81
24	600	610	40(std)	17.48	255.24
			80(XS)	30.96	441.78
			100	38.89	547.33
			120	46.02	639.58
			160	59.54	807.63

Thickness Tolerance $\pm 10\%$

HC

HC

|