

Hot Finished hollow Sections
Circular

Standard Sectional Dimension		Unit Weight
Outside Diameter (mm)	Thickness t (mm)	Kg/m
88.9	2.5	5.33
	3.0	6.36
	3.2	6.76
	3.6	7.57
	4.0	8.38
	5.0	10.35
	6.0	12.27
	6.3	12.83
	8.0	15.96
	10.0	19.46
	12.0	22.76
101.6	14.0	25.86
	3.6	8.70
	5.0	11.91
	6.3	14.81
	8.0	18.47
	10.0	22.59
	12.0	26.52
114.3	14.0	30.24
	3.0	8.23
	3.2	8.77
	3.6	9.83
	4.0	10.88
	5.0	13.48
	6.0	16.03
	6.3	16.78
	8.0	20.97
	10.0	25.72
	12.0	30.27
139.7	14.0	34.63
	16.0	38.79
	4.0	13.39
	5.0	16.61
	6.0	19.78
	6.3	20.73
	8.0	25.98
	10.0	31.99
	12.0	37.79
	14.0	43.40
	3.2	13.03
	3.6	14.62

168.3	4.0	16.21
	4.5	18.18
	5.0	20.14
	6.0	24.02
	6.3	25.17
	8.0	31.63
	10.0	39.04
	12.0	46.26
	12.5	48.03
	14.0	53.27
193.7	5.0	23.27
	6.0	27.77
	6.3	29.12
	8.0	36.64
	10.0	45.30
	12.0	53.77
	12.5	55.86
	14.0	62.04
16.0	70.12	
219.1	5.0	26.40
	6.0	31.53
	6.3	33.06
	8.0	41.65
	10.0	51.57
	12.0	61.29
	12.5	63.69
	16.0	80.14
	20.0	98.20
273	5.0	33.05
	6.0	39.51
	6.3	41.44
	8.0	52.28
	10.0	64.86
	12.0	77.24
	12.5	80.30
	14.0	89.42
	14.2	90.63
	16.0	101.41
	20.0	124.79
25.0	152.90	
323.9	5.0	39.32
	6.0	47.04
	6.3	49.34
	8.0	62.32
	10.0	77.41
	12.0	92.30
	12.5	95.99
	14.0	107.00

	14.2	108.45
	16.0	121.49
355.6	6.0	51.73
	6.3	54.27
	8.0	68.58
	10.0	85.23
	12.0	101.68
	12.5	105.77
	14.0	117.94
	16.0	134.00

HC