

shipbuilding Plate (Lloyds Grade, ABS Grade A & ABS Grade EH36 / API 2W)

Thickness	WIDTH X LENGTH	
	8' x 20'	8' x 30'
	2438mm x 6096mm	2438mm x 9144mm
mm (t)	Kg / Pc	Kg / Pc
6.0	700.16	1050.31
6.3	735.04	1102.82
6.35	741.00	1111.58
7.0	816.80	1225.36
8.0	933.44	1400.42
9.0	1050.24	1575.47
9.5	1108.66	1662.90
10	1167.00	1750.52
11	1283.70	1925.57
12	1400.41	2100.62
13	1517.11	2275.68
14	1633.80	2450.73
15	1750.50	2625.78
16	1867.20	2800.80
18	2100.60	3150.93
19	2217.30	3326.00
19.05	2223.16	3334.74
20	2334.00	3501.04
22	2567.40	3851.14
23	2684.10	4026.19
24	2800.80	4201.25
25	2917.50	4376.30
25.4	2964.22	4446.32
26	3034.23	4551.35
28	3267.60	4901.46
29	3384.30	5076.51
30	3501.00	5251.56
31.75	3705.27	5557.90
32	3734.40	5601.66
34	3967.84	5951.77
36	4201.25	6301.87
38	4434.60	6650.04
38.1	4446.32	6668.64
40	4668.06	7002.08
45	5251.56	7877.34
50	5835.07	8750.40
50.8	5928.43	8892.65
55	6418.50	9627.87
60	7002.08	10503.13
64	7468.80	11203.33
65	7585.60	11378.39
70	8169.10	12253.65
80	9336.11	14004.17
90	10503.13	15754.69
100	11670.14	17505.22
110	12837.16	19255.74

120	14004.17	21006.25
130	15171.19	22756.78
140	16338.20	24507.30
150	17505.22	26257.82

Thickness Tolerance $\pm 10\%$

HC